

UNI 1751 Dimensions

Size	For thread	d1 min.	d1 max.	d2 min.	d2 max.	h min.	h max.
	5.3 M5	5.3	5.48	9.64	10	0.9	1.1
	6.4 M6	6.4	6.62	11.57	12	1.4	1.8
	7.4 M7	7.4	7.62	13.57	14	1.4	1.8
	8.4 M8	8.4	8.62	15.57	16	1.4	1.8
	10.5 M10	10.5	10.77	19.48	20	1.8	2.2
	13 M12	13	13.27	23.48	24	2.3	2.7
	15 M14	15	15.27	27.48	28	2.3	2.7
	17 M16	17	17.27	29.48	30	2.7	3.3
	19 M18	19	19.33	33.38	34	2.7	3.3
	21 M20	21	21.33	36.38	37	2.7	3.3
	23 M22	23	23.33	38.38	39	2.7	3.3
	25 M24	25	25.33	43.38	44	3.7	4.3
	27 M26	27	27.33	49.38	50	3.7	4.3
	28 M27	28	28.33	49.38	50	3.7	4.3
	29 M28	29	29.33	49.38	50	3.7	4.3
	31 M30	31	31.39	55.26	56	3.7	4.3
	33 M32	33	33.62	58.8	60	4.4	5.6
	34 M33	34	34.62	58.8	60	4.4	5.6
	36 M35	36	36.62	64.8	66	4.4	5.6
	37 M36	37	37.62	64.8	66	4.4	5.6
	39 M38	39	39.62	70.8	72	5.4	6.6
	40 M39	40	40.62	70.8	72	5.4	6.6
	41 M40	41	41.62	70.8	72	5.4	6.6
	43 M42	43	43.62	76.8	78	6	8
	46 M45	46	46.62	83.6	85	6	8
	50 M48	50	50.62	90.6	92	7	9
	52 M50	52	52.74	90.6	92	7	9
	54 M52	54	54.74	96.6	98	7	9
	57 M55	57	57.74	103.6	105	8	10
	58 M56	58	58.74	103.6	105	8	10
	60 M58	60	60.74	108.6	110	8	10
	62 M60	62	62.74	108.6	110	8	10
	66 M64	66	66.74	113.6	115	8	10
	70 M68	70	70.74	118.6	120	9	11
	74 M72	74	74.74	123.4	125	9	11
	78 M76	78	78.74	133.4	135	9	11
	82 M80	82	82.87	138.4	140	10.8	13.2
	87 M85	87	87.87	143.4	145	10.8	13.2
	93 M90	93	83.87	158.4	160	10.8	13.2
	98 M95	98	98.87	163.4	165	10.8	13.2
	104 M100	104	104.87	173.4	175	12.8	15.2
	109 M105	109	109.87	178.4	180	12.8	15.2
	114 M110	114	114.87	183.15	185	12.8	15.2
	119 M115	119	119.87	188.15	200	12.8	15.2
	124 M120	124	125	208.15	210	14.8	17.2
	129 M125	129	130	218.15	220	14.8	17.2

134 M130	134	135	218.15	220	14.8	17.2
139 M135	139	140	228.15	230	14.8	17.2
144 M140	144	145	238.15	240	16.8	19.2
149 M145	149	150	248.15	250	16.8	19.2
155 M150	155	156	248.15	250	16.8	19.2
165 M160	165	166	248.15	250	16.8	19.2